

Gerät / Device		Anzeige- und Bedienkomponente (ABK) / Indicating and operating modules								
Model Index	Firmware K ¹ / R ²	FF Device Rev	TROVIS VIEW	DTM (FDT 1.2)	Field Communicator 375/475	Emerson DeltaV	Yokogawa Centum	Honeywell Experion PKS	ABB Industrial IT	Foxboro I/A Series
00	K 1.00 – 1.22 R 1.00 – 1.41	1	≥ 3.20	≥1.0.0	✓	≥ 6.1 ^{14,15}	✓ ^{14,15}	✓ ¹⁴	✓ ^{14,15}	✓ ¹⁴
01	K 1.21 – 1.29 R 1.41 – 1.46	1	≥ 3.20	≥1.0.0	✓	≥ 6.1 ^{14,15}	✓ ^{14,15}	✓ ¹⁴	✓ ^{14,15}	✓ ¹⁴
01	K 2.00 – 2.02 R 1.52	2	≥ 3.20	≥1.0.0	✓	≥ 8.4 ^{6,14}	✓ ^{6,14}	✓ ¹⁴	✓ ¹⁴	✓ ¹⁴
01	K 2.03 – R 1.54	2	≥ 3.20	≥1.0.0	✓	≥ 8.4 ^{6,14}	✓ ^{6,14}	✓ ¹⁴	✓ ¹⁴	✓ ¹⁴
01	K 2.04 – K2.09 R 1.55– R 1.59	2	≥ 4.21	≥1.0.0	✓	≥ 8.4 ^{6,14}	✓ ^{6,14}	✓ ¹⁴	✓ ¹⁴	✓ ¹⁴
01	K 3.00 – K3.09 R 1.61– R 1.69	3	≥ 4.66	≥1.0.2	✓	≥ 8.4 ^{6,14}	✓ ^{6,14}	✓ ¹⁴	✓ ¹⁴	✓ ¹⁴

¹ Firmware Kommunikation

² Firmware Regelung

⁶ mit Enhanced EDD

¹⁴ Device Description verfügbar über www.samsongroup.com

¹⁵ Basic Device